

## 2.8~12mm Varifocal Vandal-Resistant Ball-Mount Cameras (700 TVL, 960H High Resolution)

### EV-2706-NFGQ

2.8~12mm, 36 IR LEDs, 100' Range, Gray

### EV-2706-NFWQ

2.8~12mm, 36 IR LEDs, 100' Range, White

### Features:

- 1/3" Sony Super HAD II CCD
- 700 TV Lines
- 960H High resolution
- 2.8~12mm Lens
- 36 IR LEDs, 100ft IR range
- 360° Triple-Axis Rotation
- Heavy-duty vandal-resistant design
- Day/Night operation: 0 Lux LEDs on, 0.02 Lux LEDs off
- Cables concealed in bracket to prevent tampering
- Rugged, weatherproof (IP65) construction
- Split-glass design to eliminate IR reflection
- Mounting brackets available in white and gray

### Optional Mounting Brackets Available:

Conduit Box	Conduit Drop	Ceiling	Wall
EV-DSLGGQ* EV-DSLWQ*	EV-DDLGGQ* EV-DDLWQ*	EV-DCLGGQ* EV-DCLWQ*	EV-DWLGQ* EV-DWLWQ*
			

\*"G" in model number indicates gray; "W" in model number indicates white.



EV-2706-NFGQ



EV-2706-NFWQ

### Specifications:

Model		EV-2706-NFGQ / EV-2706-NFWQ
Chip		1/3" Sony Super HAD II CCD
Resolution		700 TV Lines
Pickup elements		976x494 (NTSC) / 976x582 (PAL)
960H*		Yes
Scanning system		2:1 Interlace
Sync		Internal
Video output		1.0V p-p composite output, 75Ω
Lens		2.8~12mm
# of IR LEDs		36 (850nm)
IR Range		Up to 100' (30m)
Minimum illumination	LEDs off	0.02 Lux
	LEDs on	0.0 Lux
S/N Ratio		>52dB
DSS (Digital Slow Shutter)		N/A
Operating voltage		12VDC
Current draw	LEDs off	100mA
	LEDs on	400mA
IP Rating		IP65
Operating temperature		-4°~131° F (-20°~55° C)
Dimensions		4 1/16" x 3 7/8" (119x98 mm)
Cable length		34" (86cm)
Weight		1-lb, 13-oz (820g)

\*In order to take full advantage of 960H resolution, the camera must be used with a 960H DVR.