

SS-077Q / SS-078Q Hold-up Button Manual



Features:

- Highly reliable switch mechanism
- Attractive, durable stainless steel housing
- Compact size
- High-security key reset
- Use with either N.C. or N.O. input
- Includes 2 keys. Spare keys also available (SS-078-KEY)

Specifications:

Model	SS-077Q	SS-078Q
Contact	N.C., push-to-open	N.O., push-to-close
Switch type	SPST	
Switch rating	1A@12VDC	
Terminal Type	Screws x2	
Mounting Type	Surface	
Dimensions	2 ³ / ₄ " x 2 ³ / ₁₆ " x 1 ¹ / ₁₆ " (70x56x27mm)	
Housing	Stainless steel	

Installation:

Please read the manual before you begin the installation

1. Remove screw on top of unit, so that the base drops out.
2. Connect wires to the 2 terminals inside back to the control unit.
3. Mount the base in the location needed.
4. Place top back on and screw down.

Overview:

SS-077Q



SS-078Q



WARRANTY: This SECO-LARM product is warranted against defects in material and workmanship while used in normal service for 1 year from the date of sale to the original customer.

NOTICE: The SECO-LARM policy is one of continual development and improvement. For that reason, SECO-LARM reserves the right to change specifications without notice. SECO-LARM is also not responsible for misprints. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. Copyright © 2019 SECO-LARM U.S.A., Inc. All rights reserved.

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606
Phone: (949) 261-2999 | (800) 662-0800

Website: www.seco-larm.com
Email: sales@seco-larm.com

 PITSW1
Order Part# 763-034-3%
ML_SS-07xQ_190213_ML.docx

ENFORCER®

SS-077Q / SS-078Q

Botón de Enclavamiento Manual



Características:

- Mecanismo de conmutación altamente confiable
- Carcasa de acero inoxidable atractiva y duradera
- Tamaño compacto
- Restablecimiento de la clave de alta seguridad
- Utilice con entrada N.C. o N.A.
- Incluye 2 llaves. Llaves de repuesto también disponibles (SS-078-KEY)

Especificaciones:

Modelo	SS-077Q	SS-078Q
Contacto	N.C. empuje para abrir	N.A., empuje para cerrar
Tipo de interruptor	SPST	
Interruptor nominal	1A@12VCC	
Tipo de terminal	Tornillos x 2	
Tipo de montaje	Superficie	
Dimensiones	2 ³ / ₄ " x 2 ³ / ₁₆ " x 1 ¹ / ₁₆ " (70x56x27mm)	
Cubierta	Acero Inoxidable	

Instrucciones de instalación:

Por favor lea el manual antes de usar el equipo.

1. Remueve el tornillo de la parte superior de la unidad para que caiga la base.
2. Conecte los 2 terminales en el interior de nuevo a la unidad de control.
3. Montar la base en la ubicación necesaria.
4. Coloque la parte superior de nuevo y atornille.

Visión General:

SS-077Q



SS-078Q



GARANTÍA: Este producto SECO-LARM está garantizado contra defectos en materiales y mano de obra mientras se usa en servicio normal durante un (1) año desde la fecha de venta al cliente original.

AVISO: La póliza de SECO-LARM es de desarrollo y mejora continua. Por esa razón, SECO-LARM se reserva el derecho de cambiar las especificaciones y los precios sin previo aviso. SECO-LARM tampoco es responsable de errores de impresión. Todas las marcas comerciales son propiedad de SECO-LARM U.S.A., Inc. o sus respectivos propietarios. Copyright © 2019 SECO-LARM U.S.A., Inc. Todos los derechos reservados.

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606
Phone: (949) 261-2999 | (800) 662-0800

Website: www.seco-larm.com
Email: sales@seco-larm.com

 PITSW1
Order Part# 763-034-3%
ML_SS-07xQ_190213_ML.docx