

Universal Door Strike

SD-996C-NUQ 12/24 VDC, Fail Secure or Fail Safe, 3 Faceplates Included

The ENFORCER Universal Door Strike can be used with virtually any cylindrical-locking system and can be configured for use in wood, aluminum, or metal doors. Included are three different-sized faceplates that can be easily installed on the strike to match the specific type of door frame.

Features:

- ▶ UL 1034 Burglary.
- ▶ Field selectable for fail-safe or fail-secure operation.
- ▶ Field selectable dual-voltage 12/24 VDC.
- ▶ Powered by a solenoid.
- ▶ Reversible non-handed design fits either right-hand or left-hand doors.
- ▶ Low profile: strike is only 1 1/4" deep for use with hollow aluminum frames.
- ▶ Includes 3 faceplates for nearly any type of door:

Frame Type	Dimensions
Aluminum	4 7/8" x 1 1/4" (124mm x 32mm)
Hollow Metal	4 7/8" x 1 1/4" (124mm x 32mm)
Wood	7 15/16" x 1 7/16" (202mm x 37mm)



SD-996C-NUQ

Specifications:

Operating voltage	12 or 24 VDC ±15%	
Current draw	12VDC	280mA @ 12VDC
	24VDC	140mA @ 24VDC
Operating temp	14° ~ 113° F (-10° ~ 45° C)	
Operating humidity	85% ±15%	

Also Available from SECO-LARM:

"No-Touch"
Request-to-Exit Sensors



SD-927PWCQ

Electromagnetic
Locks



E-941SA-1200

Stand-Alone Keypads



SK-1011-SQ

Request-to-Exit
Plates



SD-7202GC-PEQ

Access Control
Power Supply



EAP-5D1