

ENFORCER®

SR-5208

Adds the convenience of remote controlled engine starting to any vehicle alarm or keyless entry system with auxiliary outputs. Perfect for warming up the vehicle in the winter and cooling it down in the summer.

FEATURES:

- Easily connects to nearly any vehicle alarm or factory keyless entry system to add the convenience of remote starting.
- Operates with gasoline or diesel engines, and automatic or manual transmissions.
- Turns on the air conditioner or heater to ensure driving comfort.
- Attempts to start the car up to three times.
- Flashing parking light output shows when the engine is starting, running, or stopped.
- Engine will stop automatically, or can be shut down via the remote.
- Alarm (optional) remains armed while the engine is running, but external sensors and ignition sensing are bypassed to prevent false alarms.
- Safety features:
 - Neutral safety input prevents automatic transmission engines from starting if car is not in neutral.
 - Protects against over-rev and excess cranking of engine.
 - Engine will not start if the hood is open.
 - Engine shuts down if the hood is opened, the brake pedal is pressed, the transmitter is engaged, or the engine over-revs.
 - For manual transmissions, the parking brake must be set and a safety procedure must be followed when exiting the vehicle in order to remote start the engine.
- Programmable features: Tach/tachless operation, number of cylinders (1, 2, 4, 6, 8), engine crank time (2 or 10 seconds), warm-up time (6 or 18 minutes), auto/manual transmission, gasoline/diesel engine, tach signal level.
- CE approved.



Programming:

DIP Switch Settings

Switch	ON	OFF
S1 (Tach signal level)	High	Low
S5 (Crank time)	2 sec.	10 sec.
S6 (Engine run time)	6 min.	18 min.
S7 (Transmission)	Automatic	Manual
S8 (Engine type)	Gasoline	Diesel
S9 (Engine signal)	Tach	Oil/charge signal
S10 (Run signal)	Tach wire	Tachless

Number of cylinders:

	1	2	4	6	8
S2	OFF	OFF	ON	OFF	ON
S3	OFF	OFF	ON	ON	OFF
S4	OFF	ON	ON	ON	ON

The SECO-LARM policy is one of continual development and improvement. For that reason, SECO-LARM reserves the right to change specifications without notice. SECO-LARM is not responsible for misprints.

For more information, contact
SECO-LARM® U.S.A., Inc.
 16842 Millikan Avenue
 Irvine, CA 92606

Copyright ©2004 SECO-LARM U.S.A., Inc.

Tel: 1-800-662-0800 (domestic U.S. & Canada)
 Tel: 1-949-261-2999 (California & international)
 Fax: 1-949-261-7326 Email: info@seco-larm.com
 Web: www.seco-larm.com

SR-5208.pmd