

Pendant RF Transmitters

- SK-919T1-GBUQ** 1 Button, 1 Channel
- SK-919T2-GNUQ** 2 Buttons, 3 Channels
- SK-919T3-GNUQ** 3 Buttons, 7 Channels
- SK-919T4-GNUQ** 4 Buttons, 15 Channels



SK-919T1-GBUQ



SK-919T2-GNUQ



SK-919T3-GNUQ



SK-919T4-GNUQ

Features

- Operates up to 500ft (150m)*
- Over 68 billion (6.8x10¹⁰) possible codes
- LED transmission indicator appears only when buttons are pressed
- RF Anti-scan protection
- 3VDC Lithium battery included
- Compatible with all ENFORCER 315MHz receivers
- 315MHz (433.92MHz available)
- IP66 Weatherproof
- OEM/ODM Private label available
- Patented slimline design: 1 1/4"x2³/₁₆"x5⁵/₁₆" (31.5x55x8 mm)



Typical Applications



*Actual range will vary greatly depending on the installation and operating environment

OEM/ODM Private Label Available:



Custom Icons

Your Logo



- Convert your product to wireless control
- All products above are FCC, IC, and CE certified to bring your products to market faster
- We can provide custom colors, labels, icons, button configurations, and cases, all with your own logo
- Contemporary matching design allows for easy scalability as your product line expands

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright © 2025 SECO-LARM U.S.A., Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI®

PL_SK-919Tx-GxUQ_250402_ML.docx

Transmisores RF Tipo Colgante

- SK-919T1-GBUQ** 1 Botón, 1 Canal,
- SK-919T2-GNUQ** 2 Botones, 3 Canales
- SK-919T3-GNUQ** 3 Botones, 7 Canales
- SK-919T4-GNUQ** 4 Botones, 15 Canales



SK-919T1-GBUQ



SK-919T2-GNUQ



SK-919T3-GNUQ



SK-919T4-GNUQ

Funciones

- Funciona hasta 150 m (500 pies)*
- Más de 68 mil millones (6.8 × 10¹⁰) de posibles códigos
- El indicador LED de transmisión aparece solo cuando se presionan los botones
- Protección anti-escaner RF
- Incluye batería de litio de 3VCC
- Compatible con todos los receptores ENFORCER de 305MHz
- Frecuencia de operación: 315MHz (disponible con 433.92MHz)
- Resistente a la intemperie IP66
- Etiqueta privada OEM/ODM disponible
- Diseño patentado de slimline: 31.5x55x8 mm (1¹/₄"x2³/₁₆"x5¹/₁₆"

IP66 Resistente a la Intemperie	Más de 68 Mil Millones de Códigos	Indicador LED	Hasta 150m
---	---	----------------------	-------------------

Aplicaciones Típicas



Elevadores para Silla de Ruedas

Control de Acceso

Control de HVAC

Alarmas para Automóviles

Control de Portones

Etiqueta Privada OEM/ODM Disponible



Certificados por 

Iconos Personalizados

Tu Logo

- Convierte tu producto a control inalámbrico.
- Todos los productos mencionados están certificados por FCC, IC y CE para llevar tus productos al mercado más rápido.
- Podemos ofrecer colores personalizados, etiquetas, iconos, configuraciones de botones y carcasas, todo con tu propio logo.
- El diseño contemporáneo y a juego permite una fácil escalabilidad a medida que tu línea de productos se expande.

*El rango de funcionamiento real variará considerablemente según la instalación y el entorno de funcionamiento.