



SL-1301-SAQ Comparison Chart

Model	SL-1301-SAQ (current)	SL-1301-SAQ (new)
Total LEDs	54	41
LED type	Standard	Ultra-high intensity
Siren programming	Jumper	DIP Switch
Current draw	Strobe	550mA
	Steady on	550mA
	Progressive on	550mA
	Rotate clockwise	90mA
	Back and forth	90mA
	Progressive ON/OFF	550mA

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright © 2025 SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI®

PK_SL-1301-SAQ_250916_ML.docx

SL-1301-SAQ Tabla Comparativa

Modelo	SL-1301-SAQ (actual)	SL-1301-SAQ (nuevo)
Total de LEDs	54	41
Tipo de LED	Estándar	Intensidad ultraalta
Programación de sirenas	Conector de puente	Interruptor DIP
Consumo de corriente	Estroboscópico	720mA
	Encendido constante	720mA
	Encendido progresivo	720mA
	Girar en sentido horario	200mA
	De ida y vuelta	200mA
	Encendido/apagado progresivo	720mA