

# **Infrared Proximity Sensors**

CS-PD438-PQ CS-PD422-PQ CS-PD419-PQ CS-PD115-PAQ

- ø38mm, Stainless Steel / Polycarbonate
- ø22mm, Stainless Steel / Polycarbonate
- ø19mm, Stainless Steel / Polycarbonate
- ø19mm, Polycarbonate


#### **Features:**


- No-touch operation reduces the risk of spread of germs, viruses, etc., through cross-contamination
- Adjustable sensor range up to 6" (15cm) 1A relay, adjustable trigger duration 0.5~20 seconds or toggle
- Selectable LED colors (turns from red to green or green to red) to show if the sensor is activated
- Weather-resistant (IP65\*) for outdoor use


#### **Specifications:**

|                       |        | CS-PD438-PQ   | CS-PD422-PQ                 | CS-PD419-PQ   | CS-PD115-PAQ  |
|-----------------------|--------|---|-----------------------------|---------------|---------------|
| Dimensions            |        | ø11/2" (ø38mm)                                      | ø1 <sup>7</sup> /8" (ø22mm) | ø³/4" (ø19mm) | ø³/4" (ø19mm) |
| Case material         |        | Stainless steel and polycarbonate                   |                             |               | Polycarbonate |
| Operating voltage     |        | 12~24 VDC   |                             |               |               |
| Power consumption     | 12VDC  | 35mA@12VDC  | 30mA@12VDC                  | 30mA@12VDC    | 30mA@12VDC    |
|                       | 24VDC  | 45mA@24VDC  | 35mA@24VDC                  | 30mA@24VDC    | 30mA@24VDC    |
| Relay type            |        | Form C dry contact, NO/NC/COM, 1A@24VDC, 0.5A@12VAC |                             |               |               |
| Connectors            |        | Wire terminals                                      |                             |               |               |
| Response time         |        | 10mS  |                             |               |               |
| Output time           |        | 0.5~20s, toggle                                     |                             |               |               |
| Range                 |        | 1º/ <sub>16</sub> "~6" (4~15cm)                     |                             |               |               |
| LED Status indicator  |        | Selectable red/green or green/red                   |                             |               |               |
| Operating<br>life     | Relay  | 1,000,000 cycles                                    |                             |               |               |
|                       | Sensor | 100,000 hours                                       |                             |               |               |
| IP Rating             |        | IP65*   |                             |               |               |
| Operating temperature |        | -4°~131° F (-20°~55° C)                             |                             |               |               |

#### **Overview:**








#### SECO-LARM<sup>®</sup> U.S.A., Inc.


16842 Millikan Avenue, Irvine, CA 92606 **Phone:** (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com



CS-PD422-PQ Shown

## Sample Applications:






Replace mechanical switch (machinery, dispensers, medical devices, etc.)

## LED Indicators (Selectable):





#### Reffs

Copyright © 2020 SECO-LARM U.S.A, Inc. All rights reserved.

All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® **ENFORCER®** CRIMEBUSTER® CBA® **SLI® "** 

PI\_CS-PDxxx-PQ\_200617.docx

# Sensor