

## Audio/Video

# HDMI Extender over Single Cat5e/6


## MVE-AH1E1-01NQ

The ENFORCER HDMI Extender over Single Cat5e/6 extends the range of traditional HDMI cabling methods by using an active transmitter and receiver to send video and audio over a single Cat5e/6 cable. HDMI formats as large as 1080p can be transmitted up to 164ft (50m) between the two units with zero signal loss by using integrated circuits in the receiver and transmitter. The extender also supports HDMI loop output, EDID management settings, and one way IR control for remotely controlling HDMI sources and displays.

#### **Features:**

- Extend HDMI over a single Cat5e/6 cable
- Supports resolutions from 480i to 1080p with zero signal loss
- Transmits up to 164ft (50m) at 1080p over Cat5e/6 cable
- HDMI Loop output for local HDMI display
- Plug and play operation comes as a complete set
- IR Pass-through for remote control extension and operation
- EDID Management switch
- Two (2) 5VDC power supplies included

#### **Sample Application:**





## **Specifications:**

Input Video signal		3.3V
Input DDC signal		5Vp-p (TTL)
Maximum single link range		1080p
Deep color		24bit
Video formats supported		High-speed HDMI, HDCP 1.2
Audio formats supported		LPCM, Dolby-AC3, DTS7.1, DSD
Output video		HDMI
Resolutions supported		1080p/1080i/720p/576p/576i/480p/480i
Range – 1080p		Up to 164' (50m)
Video amplifier bandwidth		4.95Gbps
Video input connector		HDMI Type A 19-pin female
Maximum input cable length		24AWG (15m), 26AWG (10m), 28AWG (5m)
Video output connector		HDMI Type A 19-pin female
Maximum output cable length		24AWG (15m), 26AWG (10m), 28AWG (5m)
Cat5e/6 Wiring standard		T-568B
IR Pass-through frequency		30~60 kHz
Operating voltage		5VDC
Power supply		1A@5VDC (2 Adapters) (2.1mm plug)
ESD Protection (human body model)		±8kV (Air-gap discharge), ±4kV (contact discharge)
(human body r Current draw	Transmitter	300mA@5VDC
	Receiver	200mA@5VDC
Operating temperature		32°~104° F (0°~40° C)
Operating humidity		20~90% RH (No condensation)
Dimensions		3 <sup>1</sup> / <sub>8</sub> "x <sup>11</sup> / <sub>16</sub> "x2 <sup>5</sup> / <sub>8</sub> " (79x17x67 mm)
Weight		5.3-oz (150g) (Each)

#### SECO-LARM<sup>®</sup> U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606 Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326 Website: www.seco-larm.com Email: sales@seco-larm.com

### F© ( ( 🐵

Copyright © 2018 SECO-LARM U.S.A, Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® *ENFORCER®* CRIMEBUSTER® CBA® *SLI® JE*®

PI\_MVE-AH1E1-01NQ\_180606.docx