

3/8" Concealed-Mount Contacts, Stubby

SM-207-5Q/W

³/₈" (10mm) Gap, Closed Loop, Stubby ³/₄" (19mm) Switch and Magnet, Wire Leads, White

SM-207-5Q/BR

³/₈" (10mm) Gap, Closed Loop, Stubby ³/₄" (19mm) Switch and Magnet, Wire Leads, Brown

Features:

- Used for protecting sliding doors and windows where space is limited
- 3/8" (10mm) Press-fit mount
- 15" (38cm) Wire leads
- Contact reed switch is SPST, deactivated rhodium on gold underplating for a longer expected life
- Unique glue/epoxy compound protects reed switch
- For closed loop circuits
- 3/8" (10mm) Gap
- Lifetime limited warranty








3/8" Press-Fit 15" Wire Leads 3/8" Gap

Specifications:

Model		SM-207-5Q/W	SM-207-5Q/BR
Loop type		Closed loop	
Electrical configuration		N.O. (SPST)	
Operation gap		³ / ₈ " (10mm)	
Connectors		15" (38cm) Leads	
Color		White	Brown
Material	Case	High-impact ABS plastic/epoxy compound	
	Contact	Deactivated rhodium on gold underplating	
Contact rating		1.0A@10VDC (max.)	
		10W (max.)	
Operating temperature		-15°~160° F (-25°~70° C)	
Switch cycles		50 Million (0.1mA@5VDC)	
Switch dimensions		³ / ₄ "xø ⁷ / ₁₆ " (19xø11 mm)	
Magnet dimensions		³ / ₄ "xø ⁷ / ₁₆ " (19xø11 mm)	
Magnet		Alnico 5	

Dimensions:



SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com

