

Armored Door Cords

Installation Manual



Also Available from **SECO-LARM®**:

Door Strikes



Push-to-Exit Bars



SD-995C Shown

SD-961A-36 Shown

Deadbolts

Maglocks



E-941SA-600 Shown

SD-997B-GBQ Shown

Armored Door Cord with Plastic End Caps, Silver

SD-969-A18Q

- Plastic end caps
- Designed to carry wiring to conduct power to electric locks or access systems mounted in doors
- Mounting screws included
- Surface-mount
- 16" (41cm) Stainless steel armored cord
- Inside door-cord diameter: 5/16" (8mm)
- Outside door-cord diameter: 7/16" (11mm)



Armored Door Cord with Die-Cast Aluminum End Caps, Silver

SD-969-S18Q

- Die-cast aluminum end caps
- Designed to carry wiring to conduct power to electric locks or access systems mounted in doors
- Mounting screws included
- Surface-mount
- 17" (43cm) Stainless steel armored cord
- Inside door-cord diameter: 5/16" (8mm)
- Outside door-cord diameter: 1/2" (13mm)



WARRANTY: This SECO-LARM product is warranted against defects in material and workmanship while used in normal service for one (1) year from the date of sale to the original customer. SECO-LARM's obligation is limited to the repair or replacement of any defective part if the unit is returned, transportation prepaid, to SECO-LARM. This Warranty is void if damage is caused by or attributed to acts of God, physical or electrical misuse or abuse, neglect, repair or alteration, improper or abnormal usage, or faulty installation, or if for any other reason SECO-LARM determines that such equipment is not operating properly as a result of causes other than defects in material and workmanship. The sole obligation of SECO-LARM and the purchaser's exclusive remedy, shall be limited to the replacement or repair only, at SECO-LARM's option. In no event shall SECO-LARM be liable for any special, collateral, incidental, or consequential personal or property damage of any kind to the purchaser or anyone else.

Armored Door Cord with Terminal Blocks and Removable Die-Cast Aluminum End Caps


SD-969-T15Q/B – Bronze SD-969-T15Q/S – Silver

- Designed to conduct power to electric locks or access systems
- Once mounted, to access, simply remove cover.
 Door cord stays in place. No need to remove from the door. Prevents stripping of the screws and mounting points
- Surface-mounted
- Terminal blocks with pre-wired cables (8 connections) for quick, easy, and secure installation
- Maximum current 3A@30VAC/VDC
- 15" (39cm) Stainless steel armored cord
- Inside door-cord diameter: 5/16" (8mm)
- Outside door-cord diameter: ⁷/₁₆" (11mm)
- Security screws (included) prevent tampering
- Available in bronze or silver finish



SD-969-T15Q/S shown

Sample Wiring Diagram



Note: Each terminal is wired on a one to one basis, meaning that whatever is wired to a particular terminal number on one block will be connected to the same terminal number on the other block.

Armored Door Cord with Removable Die-Cast Aluminum End Caps

SD-969-M15Q/B - Bronze SD-969-M15Q/S - Silver

- Designed to carry wiring to conduct power to electric locks or access systems
- Once mounted, to access, simply remove cover.
 Door cord stays in place. No need to remove from the door. Prevents stripping of the screws and mounting points
- Surface-mounted
- 15" (39cm) Stainless steel armored cord
- Inside door-cord diameter: 5/16" (8mm)
- Outside door-cord diameter: ⁷/₁₆" (11mm)
- Security screws (included) prevent tampering
- Available in bronze or silver finish



SD-969-M15Q/B shown

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606 Website: www.seco-larm.com Phone: (949) 261-2999 | (800) 662-0800 Email: sales@seco-larm.com

