



Comparison Chart: SK-1123-SPQ & SK-1123-SDQ

Features:

Product	SK-1123-SPQ	SK-1123-SDQ
Master Code	1 (4-8 digits)	1 (4-8 digits)
Super User Code	1 (4-8 digits)	1 (4-8 digits)
Common User Codes	Output 1	N/A
	Output 2	N/A
User Codes/Cards*	Output 1	1000 (mix of 4-8 digit user codes and proximity card/fobs)
	Output 2	100 (mix of 4-8 digit user codes and proximity card/fobs)
Visitor Codes	50 (4-8 digits)	50 (4-8 digits)
Duress Codes	Output 1	50 (4-8 digits)
	Output 2	10 (4-8 digits)
Output Mode and Timing	Output 1	Up to 99,999 seconds (~28 hrs), toggle
	Output 2	Up to 99,999 seconds (~28 hrs), toggle
Real-Time Clock	Yes	Yes
Output #1 Auto-Disable Time	Yes	Yes
Wrong-Code System Lock-Up	60-second lockout, Duress output, 15-min lockout, off	60-second lockout, 15-min lockout, off
User Code Entry Mode	Auto (no #, same length codes) or manual (#, variable length codes)	Auto (no #, same length codes) or manual (#, variable length codes)
Keypad Sounds	On/Off	On/Off
Output Relay Activation Sounds	No beeps, 1-second beep, 2 short beeps	No beeps, 1-second beep, 2 short beeps
Door-Forced-Open Warning and Timing	On (up to 999 sec)/Off	On (up to 999 sec)/Off
Door-Propped-Open Warning and Timing	On (up to 999 sec)/Off	On (up to 999 sec)/Off
Egress Input	Yes (with multiple features)	Yes (with multiple features)
DAP	Code (no jumper)	Code (no jumper)
System Restore	Yes	Yes

*Proximity card reader only on SK-1123-SPQ

Specifications:

Product	SK-1123-SPQ	SK-1123-SDQ
Operating voltage	12-24 VAC/VDC	12-24 VAC/VDC
Current draw (at 12VDC)	Standby	66mA
	Keypress	93mA
	Output 1 active	99mA
	Output 1 & 2 active	126mA
	Total max current draw	160mA
Outputs	#1 - Form C	1A@30VDC
	#2 - Form C	1A@30VDC
	K or A	100mA@24VDC
	Duress	100mA@24VDC
	Interlock	100mA@24VDC
	Tamper	50mA@24VDC
Inputs	Egress	N.O. Ground
	Door sense	N.C. Ground
	Door inhibit	N.O. Ground
Proximity reader frequency	125kHz (EM125)	N/A
Proximity reader sensing distance	1 1/2" (38mm)	N/A
Operating temperature	-4°~158°F (-20°~70°C)	-4°~158°F (-20°~70°C)
Operating humidity	5~95% Non-condensing	5~95% Non-condensing
Dimensions (including back box)	4 15/16" x 3 1/8" x 2 1/16" (125x79x52 mm)	4 15/16" x 3 1/8" x 2 1/16" (125x79x52 mm)
Weight	1-lb 2-oz (520g)	1-lb 2-oz (520g)
Included accessories	Back box, 2x installation screws, 3x mounting screws, 3x mounting screw anchors, security wrench, diode, manual	Back box, 2x installation screws, 3x mounting screws, 3x mounting screw anchors, security wrench, diode, manual

SECO-LARM® U.S.A., Inc.

16842 Millikan Ave, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright 2016 © SECO-LARM U.S.A., Inc. All rights reserved.

All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM ENFORCER CRIMEBUSTER CBA SLI

PL_SK-1123-SPQ_SK-1123-SDQ_ComparisonChart_160205.docx