

Door Closers Comparison Chart

Model		SD-C101-SBAQ	SD-C101-SGQ	SD-C131-SQ	SD-C121-S1
					
Grade 1 construction		Yes		No	
Closing force		Size 1~6		Size 3	Size 2
Closing force adjustment		Adjustment screw		Fixed	
Sweep speed		Yes			
Latch range		15°~0°			
Latch speed		Yes			
Back check		Yes		No	
No. of valves		1 Sweep, 1 latch, 1 back check		1 Sweep, 1 latch	
Handed		Reversible, non-handed design			
Door specifications	Width	32"~60" (800~1,500 mm)		Up to 42" (1070mm)	
	Weight	45~330-lb (20~150 kg)		Up to 140-lb (65kg)	Up to 100-lb (45kg)
	Type	Metal or wood			
Max. door opening – hinge side		180°	130°	120°	
Fire & smoke check doors		Yes			No
Installation		Tri-pack-regular, top jamb, and parallel arms		Regular, top jamb	
Cover		Yes	No		
Finish		Silver			
Parallel arm accessories		Yes		No	
Certifications		UL, CE, RoHS	UL, RoHS	RoHS	
Construction		Cast aluminum body, forged steel arm			
Footprint		12"x3/4" (304.8x19 mm)	9 1/16"x3/4" (230x19 mm)	6 9/16"x3/4" (166x19 mm)	5 3/16"x3/4" (132x19 mm)
Weight		4-lb (1.83kg)	3.5-lb (1.58kg)	3-lb (1.36kg)	2.25-lb (1.02kg)
Warranty		5 years			1 year

Cuadro Comparativo de Cierrapuertas

	SD-C101-SBAQ	SD-C101-SGQ	SD-C131-SQ	SD-C121-S1
Modelo				
Construcción grado 1	Sí		No	
Fuerza de cierre	Tamaño 1 ~ 6		Tamaño 3	Tamaño 2
Ajuste de la fuerza de cierre	Tornillo de ajuste		Fija	
Velocidad de barrido	Sí			
Rango de cierre	15°~0°			
Velocidad de cierre	Sí			
Corregir	Sí		No	
Número de válvulas	1 barrido, 1 pestillo, 1 retención trasera		1 barrido, 1 pestillo	
Entregada	Diseño reversible y sin manos.			
Especificaciones de la puerta	Ancho	32"~60" (800~1,500 mm)		Hasta 42" (1070mm)
	Peso	45~330-lb (20~150 kg)		Hasta 140 libras (65 kg) Hasta 100 libras (45 kg)
	Tipo	metal o madera		
Máx. apertura de puerta – lado bisagras	180°	130°	120°	
Puertas cortafuego y humo	Sí			No
Instalación	Paquete triple: brazos regulares, de jamba superior y paralelos		Jamba superior normal	
Cubrir	Sí	No		
Acabado	Plata			
Accesorios para brazos paralelos	Sí		No	
Certificaciones	UL, CE, RoHS	UL, RoHS	RoHS	
Construcción	Cuerpo de aluminio fundido, brazo de acero forjado			
Huella	12"x3/4" (304.8x19 mm)	9 ¹ / ₁₆ "x3/4" (230x19 mm)	6 ⁹ / ₁₆ "x3/4" (166x19 mm)	5 ³ / ₁₆ "x3/4" (132x19 mm)
Peso	4-lb (1.83kg)	3.5-lb (1.58kg)	3-lb (1.36kg)	2.25-lb (1.02kg)
Garantía	5 años			1 año