






### No-Cut Door Strike Comparison Chart

	SD-995C-D3F	SD-995C-D3Q	SD-991A-D1Q
<b>Model</b>			
<b>Fire Rating</b>	3 Hour Fire Rating. Must be used in Fail-Secure mode	None	None
<b>Certification</b>	ETL: NFPA 252, CAN/ULC-S104, UL 10C, UL 10B	UL 1034	None
<b>Operating Temperature</b>	14°~120° F (-10°~49° C)	14°~120° F (-10°~49° C)	14°~120° F (-10°~49° C)
<b>Endurance</b>	1,000,000 cycles (Factory Tested)	250,000 cycles (UL Tested), 1,000,000 cycles (Factory Tested)	250,000 cycles (Factory Tested)
<b>Latch Throw</b>	3/4" (19mm)	9/16" (15mm)	1/2" (13mm)
<b>Weight</b>	11.3-oz (320g)	11.25-oz (319g)	4.75-oz (135g)
<b>Dimensions</b>	47/8"x11/4"x11/16" (124x32x27.5 mm)	47/8"x11/4"x11/16" (124x32x27.5 mm)	11/8"x23/4"x15/16" (124x32x27.5 mm)

## Tabla Comparativa de Cerraduras para Puertas Sin Corte

	SD-995C-D3F	SD-995C-D3Q	SD-991A-D1Q
<b>Modelo</b>			
<b>Clasificación contra incendios</b>	Clasificación contra incendios de 3 horas. Debe utilizarse en modo de cerrado en fallo (Fail-Secure)	Ninguna	Ninguna
<b>Certificación</b>	ETL: NFPA 252, CAN/ULC-S104, UL 10C, UL 10B	UL 1034	Ninguna
<b>Temperatura de funcionamiento</b>	14°~120° F (-10°~49° C)	14°~120° F (-10°~49° C)	14°~120° F (-10°~49° C)
<b>Resistencia</b>	1,000,000 ciclos (probado en fábrica)	250,000 ciclos (probado por UL), 1,000,000 ciclos (probado en fábrica)	250,000 ciclos (probado en fábrica)
<b>Recorrido del pestillo</b>	3/4" (19mm)	9/16" (15mm)	1/2" (13mm)
<b>Peso</b>	11.3-oz (320g)	11.25-oz (319g)	4.75-oz (135g)
<b>Dimensiones</b>	47/8"x11/4"x11/16" (124x32x27.5 mm)	47/8"x11/4"x11/16" (124x32x27.5 mm)	11/8"x23/4"x15/16" (124x32x27.5 mm)