




No-Cut Door Strike Comparison Chart

| | SD-995C-D3F | SD-995C-D3Q | SD-991A-D1Q |
|----------------------|---|--|---|
| Model |  |  |  |
| Fire Rating | 3 Hour Fire Rating. Must be used in Fail-Secure mode | None | None |
| Certification | ETL: NFPA 252, CAN/ULC-S104, UL 10C, UL 10B | UL 1034 | None |
| Endurance | 1,000,000 cycles (Factory Tested) | 250,000 cycles (UL Tested), 1,000,000 cycles (Factory Tested) | 250,000 cycles (Factory Tested) |
| Latch Throw | 3/4" (19mm) | 9/16" (15mm) | 1/2" (13mm) |
| Weight | 11.3-oz (320g) | 11.25-oz (319g) | 4.75-oz (135g) |
| Dimensions | 47/8"x11/4"x11/16" (124x32x27.5 mm) | 47/8"x11/4"x11/16" (124x32x27.5 mm) | 11/8"x23/4"x15/16" (124x32x27.5 mm) |

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com






Copyright © 2025 SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI®

PK_SD-99xx-Dxx_251007_ML.docx

Tabla Comparativa de Cerraduras para Puertas Sin Corte

| | SD-995C-D3F | SD-995C-D3Q | SD-991A-D1Q |
|---------------------------------------|--|--|---|
| Modelo |  |  |  |
| Clasificación contra incendios | Clasificación contra incendios de 3 horas. Debe utilizarse en modo de cerrado en fallo (Fail-Secure) | Ninguna | Ninguna |
| Certificación | ETL: NFPA 252, CAN/ULC-S104, UL 10C, UL 10B | UL 1034 | Ninguna |
| Resistencia | 1,000,000 ciclos (probado en fábrica) | 250,000 ciclos (probado por UL), 1,000,000 ciclos (probado en fábrica) | 250,000 ciclos (probado en fábrica) |
| Recorrido del pestillo | 3/4" (19mm) | 9/16" (15mm) | 1/2" (13mm) |
| Peso | 11.3-oz (320g) | 11.25-oz (319g) | 4.75-oz (135g) |
| Dimensiones | 47/8"x11/4"x11/16" (124x32x27.5 mm) | 47/8"x11/4"x11/16" (124x32x27.5 mm) | 11/8"x23/4"x15/16" (124x32x27.5 mm) |