

Miniature 1-Channel 433.92MHz RF Receivers



SK-910RG1-4 1 Channel, 1 Form C Relay

SK-910RG1-L4 3~13.8 VDC, 1 Channel, 1 Transistor GND

ENFORCER Miniature 1-Channel 433.92MHz RF Receivers provide the features you need in a miniature housing small enough to fit inside a standard conduit box. They include 4 selectable output modes, Form C or transistor ground outputs, and flexible 12/24 VAC/VDC* or 3~13.8 VDC very low voltage models.



SK-910RG1-4 shown

Features

- Compact housing, small enough to fit inside a standard conduit box
- Mounting tabs scored for easy removal
- Flexible 12/24 VAC/VDC* or 3~13.8 VDC operating voltage models
- Learn up to 8 transmitter button codes
- Range†: Up to 330ft (100m)
- Pushbutton transmitter code learning/deleting
- 4 Independently switchable output modes – 1s (default), 10s, 30s, or toggle
- 7A Form C relay (NO/NC/COM) or transistor ground (3A@12VDC)
- Compatible with all ENFORCER 433.92MHz transmitters

12/24
VAC/VDC
or
3~13.8
VDC

4
Output
Modes

Mini
Size

Up to
330ft

Specifications

Model	SK-910RG1-4	SK-910RG1-L4
Operating frequency	433.92MHz	
Certifications	FCC, CE, IC, RoHS	
Memory capacity	Up to 8 button codes	
Operating voltage	12/24 VAC/VDC*	3~13.8 VDC
Current draw (max.)	Standby	10mA@12VDC
	Active	60mA@12VDC
Channels	Standby	7mA@12VDC
	Active	8mA@12VDC
Outputs	Channels	1
	# of Outputs	1
	Type	Form C relay output
	Rating	20A@14VDC / 7A@120VAC
Modes	Rating	3A
	Modes	Timed – 1s (default), 10s, 30s; or toggle
RF range†	Up to 330ft (100m)	
Connectors	Exposed screw terminals	
LED Indicators	Blue – channel	
Antenna	Built-in, inside case	
Operating humidity	5~95%, non-condensing	
Operating temperature	-40°~167° F (-40°~75° C)	
Dimensions (without tabs)	1 ¹¹ / ₁₆ "x7 ⁷ / ₈ "x1 ¹¹ / ₁₆ " (43x23x43 mm)	

Miniature Size

Fits into standard conduit and electrical boxes



*24VAC/VDC is selectable by cutting a jumper.

†Actual operating range will vary greatly depending on the installation and operating environment.

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright © 2026 SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI®

PL_SK-910RG1-x4_260911_ML.docx

Receptores RF Miniatura de 1 Canales 433.92MHz

SK-910RG1-4 1 Canal, 1 Relé Forma C

SK-910RG1-L4 3~13.8 VCC, 1 Canal, 1 Transistor GND

Los Receptores RF Miniatura ENFORCER de 1 Canales 433.92MHz ofrecen las funciones necesarias en una carcasa compacta, lo suficientemente pequeña para caber dentro de una caja de conduit estándar. Incluyen 4 modos de salida programables, salidas de relé Forma C o transistor a tierra, así como modelos con voltaje flexible de 12/24 VCA/VCC* o de muy bajo voltaje de 3~13,8 VCC.

Características

- Carcasa compacta, lo suficientemente pequeña para caber dentro de una caja de conduit estándar
- Orejas de montaje marcadas para fácil desprendimiento
- Modelos con voltaje de operación flexible de 12/24 VCA/VCC* o 3~13,8 VCC
- Aprende hasta 8 códigos de botones de transmisor
- Alcance†: Hasta 330 pies (100m)
- Aprendizaje/eliminación de códigos de transmisores mediante botón
- 4 modos de salida conmutables de forma independiente – 1s (predeterminado), 10s, 30s o conmutación
- Relé tipo C de 7 A (NA/NC/COM) o transistor a tierra (3A a 12VCC)
- Compatible con todos los transmisores ENFORCER de 433.92MHz

Especificaciones

Modelo		SK-910RG1-4	SK-910RG1-L4
Frecuencia		433.92 MHz	
Certificaciones		FCC, CE, IC, RoHS	
Capacidad de memoria		Hasta 8 códigos de botón	
Voltaje de operación		12/24 VCA/VCC*	3~13,8 VCC
Consumo de corriente (máx.)	En espera	10mA a 12VCC	7mA a 12VCC
	Activo	60mA a 12VCC	8mA a 12VCC
Canales		1	1
Salidas	Numero	1	1
	Tipo	Salida de relé Forma C	Salida de transistor a tierra
	Clasificación	20A a 14VCC / 7A a 120VCA	3A
	Modos	Temporizado de 1 s (predeterminado), 10s, 30s; o alternar	
Alcance de RF†		Hasta 330 pies (100m)	
Conectores		Terminales de tornillo expuestos	
LED Indicadores		Azul – canal	
Antena		Integrado, dentro de la carcasa	
Humedad de operación		5~95%, no condensación	
Temperatura de operación		-40°~75° C (-40°~167° F)	
Dimensiones (sin pestañas)		43x23x43 mm (1 ¹¹ / ₁₆ "x1 ⁷ / ₈ "x1 ¹¹ / ₁₆ ")	

*La operación a 24 VCA/VCC se selecciona cortando un puente. †El alcance de funcionamiento real variará considerablemente según la instalación y el entorno de funcionamiento.

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Webseite: www.seco-larm.com Email: sales@seco-larm.com



SK-910RG1-4 mostrado

12/24
VCA/VCC
o
3~13,8
VDC

4
Modos de
Salidas

Tamaño
Mini

Hasta
100m

Tamaño Miniatura

Se adapta a cajas estándar de conduit y eléctricas

